

Fig. 1a. Model of generation of inter-bin interference in windowed DMT receiver

002050-11195500




Fig. 1b. Model of noise coloration in windowed DMT receiver

000000-FIG-1b




Fig. 2. Illustration of MLSE PRS decoding with noise cancellation in windowed DMT receiver with TEQ.




Fig. 3. Illustration of MLSE decoding and noise cancellation in windowed DMT receiver with per-bin equalizer TEQ eliminated, largely simplified or replaced by a simple compromising corrector, $C(f)$, of telephone line amplitude characteristic.

000000-11133500




Fig.4. Principal block diagram of noise prediction procedure

000090-1779560




Fig. 5. 4-state trellis diagram corresponding to in-phase or quadrature part of 2-bit constellations; data symbols at c_i tap location of Fig. 1 are presented as samples to the right within brackets.

0022090-77738560





Fig. 6. 16-level trellis diagram for in-phase or quadrature components of 4-bit constellations; symbols at c_1 tap location of Fig. 1 are presented as samples to the right within brackets.

Fig. 7. Bit error probability for MLSE decoding;
DFE is MLSE with decoding depth 1



002090-TH98360




Fig. 8. An example of trellis diagram for abrupt change of number of bits between K-th and (K+1)-st bin from 4 to 2.

002030-149550




Fig. 9. An example of backward trellis procedure; the last two symbols prior to sending k-th bin symbol are taken to be 1 and 1; the symbols transmitted on bins from k to k+5 are taken to be 1, -1, -1, 1, -1 and -1 so that correct path is shown by bold line; decoding depth is 6.

002090-1495560




Fig.9a. Illustration of LMS estimation of predictor coefficients

Questions
Answers
Exercises
Homework
**TInterpretations
Problems
References
Studies
Vocabulary
Working Papers
Zeroes**




Fig. 10. An example of backward trellis procedure; the last two symbols prior to sending k-th bin symbol are taken to be 0 and 0; the symbols transmitted on bins from k to k+5 are taken to be 1, -1, -1, 1, -1 and -1 so that correct path is shown by bold line; decoding depth is 6. State transition values for first two trellis stages are different from those in table 1 and are shown here.




Fig. 11. An example of exhaustive MLSE procedure in case of four active bins separated from other symbols by two zero valued bins; the symbols transmitted on bins from k to $k+3$ are taken to be 1, -1, -1 and 1 so that correct path is shown by bold line; State transition values for auxiliary first two and the last two trellis stages are different from those in table 1 and are shown here.